

G500™ Filtration System for the **Perfect Coffee**

A compact, state-of-the-art RO system specifically designed to supply the perfect water for gourmet coffee preparation




Features and Benefits

- High flow rate delivers up to 1500 liters per day of ultrapure drinking water
- Five-stage filtration technology removes heavy metals, chemicals, organics and other impurities
- Advanced final stage remineraliser adjusts pH and hardness to industry-recognised optimum levels for coffee brewing
- Patented modular system for easy filter swap-out within seconds
- Optional 60 liter (14 gallons) RO storage tank available for high demand usage

GWS has perfected this difficult water preparation using the G500 for coffee

Alkalinity



Hardness



Advanced water supply system for high-end coffee machines

Stunningly compact and environmentally friendly, the G500 reverse osmosis purification system provides the purest water for the most discerning baristas. Designed for use with high-end commercial espresso machines, the G500's patented multi-stage system first removes any residual tastes, odours and impurities from the water source. The water then passes through a final stage where the pH and hardness are adjusted to SCA-recommended levels, ensuring the perfect balance.

With the G500 we refined, re-imagined, and re-engineered everything you know about water purification from inside out. The result is an elegant all-in-one RO water purification system that is as much a work of art as it is a state-of-the-art purification system. The G500 is a must have if you want perfect water for your coffee.

Unique design

- Compact size 44cm(L) x 26cm(W) x 44cm(H) ensures maximum use of your under-counter or display space
- Patented cabinet design uses the highest-quality fiberglass-reinforced nylon for durability and long service life
- Dual pressure gauges for monitoring system pressure & incoming water pressure
- Patented self-aligning filter cartridges with unique built-in handles for easy insertion and removal



Enhanced & environmentally friendly

- Water recovery rate exceeds ASSE 1086 efficiency standard
- Dry-run protection with auto-restart
- Auto-flush function: 5 minute timer prevents clogging the RO membrane, ensuring a long service life
- Durability: premium grade fittings & connections ensures reliability

Versatile & user friendly

- Quick and easy filter replacement design prevents messy spillage
- Compact easy-to-use filter cap removal tool
- Effortless filter alignment system
- Integrated filter life monitoring system
- Built-in LED status indicator
- Can be used as a direct flow system or in conjunction with an RO tank



Specifications

Product Series Name	G500™ for Coffee
Dimensions	44 x 26 x 44 cm / 16.5 x 10.2 x 17.3 inch
Weight	19 kg / 41.9 lb
Maximum Tube Size	3/8"
Operating Pressure	1.4 - 4 bar 20 - 60 psi
Max. Pump Pressure	8.6 bar 125 psi
Power Input	110V 60Hz / 230V 50Hz / 60Hz
Power Consumption	36V DC / 2A
Operating Temperature	5°C - 38°C / 41°F - 100°F
Maximum TDS	2,000 ppm
Maximum Hardness	291 ppm (17 grains per gallon)
Maximum Iron	0.3 ppm
Maximum Manganese	0.05 ppm
Maximum Turbidity	2 NTU
Chlorine	0.2~1.0 ppm
рН	6.0~8.5





